

SINCE 1889



Yamato Scientific
America

2026

PRODUCT DIGEST

GENERAL LABORATORY INSTRUMENTS

www.yamato-usa.com

BATHS

Water Baths



BM SERIES	Temperature range	Internal capacity
BM100/110	RT +5~95°C	4L
BM401		7L



BM SERIES	Temperature range	Internal capacity
BM302A/312A	RT +10~90°C	5L

Oil Baths



BO SERIES	Temperature range	Bath capacity
BO302A/312A	RT +10~180°C	5L



BO SERIES	Temperature range	Bath capacity
BO601	RT +5~180°C	7L



BOG SERIES	Temperature range	Bath capacity
BOG100/110	RT +5~240°C	1L
BOG200/210		2.2L



BOS SERIES	Temperature range	Bath capacity
BOS100/110	RT +5~250°C	1L
BOS200/210		2.2L

BATHS



BOA SERIES	Temperature range	Bath capacity
BOA311	RT +10~270°C	37L

CUSTOMIZED INDUSTRIAL PRODUCTS

Large Autoclave



YYK SERIES	Operating temp. range	Internal dimension
YYK500	RT +10~70°C	ø500mm x 850Lmm
YYK750		ø750mm x 1100Lmm
YYK800		ø800mm x 1100Lmm
YYK900		ø900mm x1300Lmm
Customized chamber dimension		

CUSTOMIZED INDUSTRIAL PRODUCTS

Combination Forced Convection Oven



C1-006	Temperature range	Internal dimensions
	RT +10~260°C	W700xD500x500mm (single)
Platform stands to combine units / Customized chamber dimensions		

Large Walk-in Forced Convection Oven



C4-008	Temperature range	Internal dimensions
	RT +10~100°C	W3500xD3500x3000mm
Double door structure / Anti-lock mechanism		

Fully Automatic Conveyor Drying Oven



C1-007	Temperature range	Conveyor speed
	RT +20~80°C	0.035 - 0.35 m/min
Adjustable conveyor speed capable of multiple treatment processes		

Large Capacity Low Temperature Chamber



YY-711	Temperature range	Internal capacity
	-20~50°C	800L
Size can be specified according to needs		

DATA LOGGERS



GL SERIES	Sampling interval	Number of channels
GL260	10ms - 1h	10 isolated analog channels
GL860	5ms-1h	20 standard analog channels, expandable to 200

DESICCATORS

Clear Acrylic

NEW!



PLA SERIES	Dimensions	Number of cubicles
PLA-8605CGNS	12" x 12" x 6" high	1
PLA-860CGNS	12" x 12" x 12" high	1
PLA-861CGNS	12" x 12" x 24" high	2
PLA-8615CGNS	12" x 12" x 24" high	1
PLA-862CGNS	18" x 18" x 18" high	2
PLA-863CGNS	24" x 18" x 24" high	2

Amber Acrylic (for light sensitive materials)

PLA SERIES	Dimensions	Number of cubicles
PLA-8605CGANS	12" x 12" x 6" high	1
PLA-860CGANS	12" x 12" x 12" high	1
PLA-861CGANS	12" x 12" x 24" high	2
PLA-8615CGANS	12" x 12" x 24" high	1
PLA-862CGANS	18" x 18" x 18" high	2
PLA-863CGANS	24" x 18" x 24" high	2

FREEZERS: LOW TEMP. UP TO -40°C

Laboratory Freezers - Undercounter

UCF SERIES	Temperature Range	Capacity
UCF000	-20°C	1.5ft³ / 42L
UCF001	-15°C to -25°C	1.7ft³ / 48L
UCF101A	-10°C ~ -25°C	3.2ft³ / 90L
UCF101B	-20°C ~ -40°C	3.2ft³ / 90L



UCF000



UCF001

FREEZERS: LOW TEMP. UP TO -40°C

Laboratory Freezers - Undercounter



UCF101A



UCF101B

FREEZER / REFRIGERATOR COMBINATION

RFC SERIES	Temperature Range	Capacity
RFC501	(Refrigerator) 2°C to 8°C (Freezer) 0°C to -25°C	9.1ft ³ Refrigerator 9.1ft ³ Freezer
RFC1301	(Refrigerator) 2°C to 8°C (Freezer) 0°C to -25°C	24ft ³ Refrigerator 24ft ³ Freezer
RFC2001	(Refrigerator) 4°C / 39°F (Freezer) -20°C	46.6ft ³ Refrigerator 24ft ³ Freezer



RFC1301



RFC2001

FREEZERS UP TO -85°C

Ultra Low Temperature Freezers - Chest Style

VUF SERIES	Temperature Range	Capacity
VUF101C	-40°C ~ -85°C	3ft ³ / 83L
VUF201C		5ft ³ / 142L
VUF301C		9ft ³ / 255L
VUF401C		12ft ³ / 340L
VUF501C		14ft ³ / 400L
VUF601C		17ft ³ / 480L
VUF801C	-40°C ~ -85°C	22ft ³ / 626L
VUF901C	-40°C ~ -80°C	27ft ³ / 766L

Features:

- Touch screen control
- Hi/Low alarm with email and SMS notification
- Viewable temperature graph
- Data logging downloadable via USB or FTP
- Multi-level security
- VNC remote access via PC / smart devices



VUF101C



VUF201C



VUF401C



VUF601C



VUF901C

FREEZERS UP TO -85°C

Ultra Low Temperature Freezers - Upright Style

VUF SERIES	Temperature Range	Capacity
VUF401U	-40°C ~ -85°C	13ft³ / 370L
VUF501U		18ft³ / 505L
VUF601U		22ft³ / 626L
VUF701U		25ft³ / 710L
VUF901U	-40°C ~ -80°C	31ft³ / 877L

Features:

- Touch screen control
- Hi/Low alarm with email and SMS notification
- Viewable temperature graph
- Data logging downloadable via USB or FTP
- Multi-level security
- VNC remote access via PC / smart devices



FREEZERS UP TO -40°C

Low Temperature Freezers - Chest Style

VLF SERIES	Temperature Range	Capacity
VLF001C	0°C ~ -40°C	2ft³ / 56L
VLF101C		3ft³ / 83L
VLF201C		5ft³ / 142L
VLF301C		9ft³ / 255L
VLF401C		12ft³ / 340L
VLF501C		14ft³ / 400L
VLF601C		17ft³ / 480L
VLF701C		21ft³ / 595L
VLF801C		22ft³ / 626L
VLF901C		27ft³ / 766L

Features:

- Touch screen control
- Hi / Low alarm with email and SMS notification
- Viewable temperature graph
- Data logging downloadable via USB or FTP
- Multi-level security
- VNC remote access via PC / smart devices



VLF101C



VLF201C



VLF301C



VLF401C



VLF601C



VLF901C

FREEZERS UP TO -40°C

Low Temperature Freezers - Upright Style

VLF SERIES	Temperature Range	Capacity
VLF401U	0°C ~ -40°C	13 ft ³ / 370L
VLF501U		18 ft ³ / 505L
VLF601U		22 ft ³ / 626L
VLF701U		25 ft ³ / 710L
VLF801U		28 ft ³ / 792L

Features:

- Touch screen control
- Hi / Low alarm with email and SMS notification
- Viewable temperature graph
- Data logging downloadable via USB or FTP
- Multi-level security
- VNC remote access via PC / smart devices



VLF401U



VLF501U



VLF701U



VLF801U

GLASSWARE WASHERS



AW SERIES	Capacity	Washing water temp.
AW47	Test tube 450 pcs. (16.5 ml) Volumetric flasks 36 pcs. (100 ml)	Room Temp ~60°C



AWD SERIES	Capacity	Washing water temp.
AWD-510 / 510DRY (pre-drying)	Glassware as a whole: test tubes, flasks, beakers (excluding pipet)	45~93°C

GLOVE BOXES

Compact Glove Boxes



SG SERIES	Width (inside dimension)	No. of gloves
SG828	28"	2
SG835	35"	2
SG848	48"	3
SG860	60"	4



Anaerobic Chambers



AC SERIES	Hypalon gloves	Approximate volume
AC505/515	One (1) pair	17.3 cubic ft. / 489L
AC706/716	Two (2) pairs	40.9 cubic ft. / 1157L



AC SERIES	Hypalon gloves	Approximate volume
AC505A/515A	One (1) pair	17.3 cubic ft. / 489L
	One -Touch, "Go Anaerobic" button to initiate purging sequence	

BESTSELLER INCUBATORS

Natural Convection



IC SERIES	Temperature range	Internal capacity
IC103CW/113CW	RT +5~80°C	37L
IC403CW/413CW		97L
IC603CW/613CW		159L
IC803CW/813CW		318L
IC903CW/913CW		567L



MUFFLE FURNACES



FO SERIES	Temp range	Capacity	FO SERIES	Temp range	Capacity
FO101CR/111CR	100~1150°C	1.5L	FO511CR	100~1150°C	11.3L
FO201CR/211CR		3.75L	FO611CR		17.5L
FO301CR/311CR		7.5L	FO711CR		23.6L
FO411CR		9L	FO811CR		30L




FP SERIES	Temperature range	Internal capacity
FP103	100~1150°C	1.5L
FP303/313		7.5L
FP413		11.3L

OVENS

Natural Convection Ovens



DX SERIES	Temperature range	Internal capacity
DX302C/312C	RT +5~300°C	28L
DX402C/412C		74L
DX602C/612C	RT +5~280°C	153L



DVS SERIES	Temperature range	Internal capacity
DVS402C/412C	RT +5~260°C	99L
DVS602C/612C		162L




DR SERIES	Temperature range	Internal capacity
DR-201-115V	300~700°C	13.75L
DR-201-220V		



DG SERIES	Temperature range	Internal capacity
DG400C/410C	RT +5~70°C	92L
DG440C/450C		
DG800C/810C		445L
DG840C/850C		

OVENS

Forced Convection Ovens



DKM SERIES	Temperature range	Internal capacity
DKL301C/311C	RT +10~260°C	27L
DKL401C/411C		90L
DKL601C/611C		150L



DKN SERIES	Temperature range	Internal capacity
DKN-303-115V DKN-303-220V	RT +10~260°C	27L



DKV SERIES	Temperature range	Internal capacity
DKV400/410	RT +10~270°C	90L
DKV600/610		150L
DKV810		300L
DKV910	RT +10~220°C	545L



DNE SERIES	Temperature range	Internal capacity
DNE401/411	RT +20~210°C	90L
DNE601/611		150L
DNE811	RT +15~210°C	300L
DNE911		540L



DNF SERIES	Temperature range	Internal capacity
DNF301	RT +15~260°C Wind velocity 1~10	27L
DNF401/411		90L
DNF601/611		150L
DNF811		300L
DNF911		540L

OVENS

Fine Ovens



DF SERIES	Temperature range	Internal capacity
DF412	RT +15~260°C	91L
DF612		216L
DF832		512L
DF1032	RT +15~200°C	1000L

DH SERIES	Temperature range	Internal capacity
DH412	RT +15~360°C	91L
DH612		216L
DH832		512L
DH1032	RT +15~300°C	1000L



DH SERIES	Temperature range	Internal capacity
DH650Z	RT +10~500°C	216L

Inert Ovens



DN SERIES	Temperature range	Internal capacity
DN411IE	RT +15~360°C	95L
DN611IE		223L

OVENS

Vacuum Ovens

BESTSELLER



ADP SERIES	Temperature range	Internal capacity
ADP200C/210C	40~240°C	10L
ADP300C/310C		27L



SDP SERIES	Temperature range	Internal capacity
SDP300/310	RT +10~220°C	47.2L
SDP400/410		127.4L
SDP610	RT +15~220°C	264L

BESTSELLER



DP SERIES	Temperature range	Internal capacity
DP43C	40~200°C	91L
DP63C		216L



DP SERIES	Temperature range	Internal capacity
DP83C	40~200°C	512L
DP104C		1000L

Clean Ovens



DE/DT SERIES	Temperature range	Internal capacity
DE411	RT +30~260°C	91L
DE611		216L
DT411	RT +30~360°C	91L
DT611		216L



DES/DTS SERIES	Temperature range	Internal capacity
DES830	RT +30~260°C	327L
DTS830	RT +30~360°C	

PCR WORKSTATIONS



PCR SERIES	Features	Inside dimension
PR204/214	"Bright Light" illumination system (40,000 hour lamp guarantee) U.V. germicidal system rated at 254 nm	23.5" x 17" x 21" / 597 x 432 x 530 mm



PCR SERIES	Features	Inside dimension
PR204H/214H	"Mini HEPA" filter size 4" x 9.5" x 1" thick "Bright Light" illumination system (40,000 hour lamp guarantee) U.V. germicidal system rated at 254 nm	23.5" x 17" x 21" / 597 x 432 x 530 mm

PLASMA TREATER

Precision Surface Treatment



PSA SERIES	No. of heads	Operating temperature
PSA110	1	22°C ~ 40°C
PSA210	2	
PSA310	3	
PSA410	4	

REFRIGERATORS

Undercounter and Countertop Refrigerators



UCR001



UCR101G

UCR SERIES	Temperature Range	Capacity
UCR001	2°C ~ 8°C	2.64ft³ / 75L
UCR001G		2.64ft³ / 75L
UCR101		4.6ft³ / 130L
UCR101G		4.6ft³ / 130L

ROTARY EVAPORATORS

Basic & Economical



RE SERIES	Water/Oil bath capacity	Rotation speed
RE202A/212A	5L	5~315 rpm

Standard (with vacuum controller)



REV SERIES	Water/Oil bath capacity	Rotation speed
REV202MA/212MA	5L	5~315 rpm

SHAKERS



MK SERIES	Shaking mode	Shaking frequency
MK161	Rotary, elliptical, reciprocate	20~200 rpm



SA SERIES	Shaking speed: horizontal	Shaking speed: vertical
SA300	20~300 rpm	20~300 rpm
SA320	20~210 rpm	20~210 rpm
SA400	Not applicable	20~300 rpm

SPRAY DRYERS

Compact & Economical



ADL311SA	Evaporated water amount	Temp. control range
	Max. 1300 mL/h	40~220°C

Versatile



GB210A	Evaporated water amount	Temp. control range
	Max. 1300 mL/h	40~220°C

Large Capacity



DL410	Evaporated water amount	Temp. control range
	Max. 3000 mL/h	40~300°C

Granulator



GB210B	Granulation processing capacity	Temp. control range
	50 to 300g	40~220°C

Organic Solvent Washing Unit



GWS410	Maximum flow	Storage tank capacity
	15L / min	35L

STERILIZERS

Steam Sterilizers

BESTSELLER



SK SERIES	Temperature range	Internal capacity
SK102C/112C	50~126°C	18L
SK201C/211C		24L
SK301C/311C		30L

BESTSELLER



SN SERIES	Temperature range	Internal capacity
SN300C/310C	45~135°C	32L
SN500C/510C		47L

BESTSELLER



SQ SERIES	Temperature range	Internal capacity
SQ500C/510C	45~135°C	50L
SQ811C	45~138°C	80L



SQL SERIES	Temperature range	Internal capacity
SQL1010C	45~135°C	110L

Steam Sterilizers with Dryer

BESTSELLER



SM SERIES	Temperature range	Internal capacity
SM201/211	Sterilization 105 to 123°C Drying 150 to 180°C	20L
SM301/311	Sterilization 105 to 128°C	32L
SM501/511	Drying 150 to 180°C	47L



SM SERIES	Temperature range	Internal capacity
SM520/530	45~60°C (retain temp.) 45~80°C (preheat temp.) 105~135°C (sterilize)	50L
SM820/830	60~110°C (liquefy) 135~150°C (dry)	80L

STERILIZERS

Dry Sterilizers



SK SERIES	Temperature range	Internal capacity
SK401	RT +5~260°C	99L
SK601	RT +5~260°C	162L
SK801/811	RT +5~210°C	300L

STIRRERS



LT / LR SERIES	Maximum speed	Viscosity of sample
LT400	1200 rpm	Low to high
LT500	1200 rpm	Medium to high
LR500A	340 rpm	Low to high
LR500B	1000 rpm	Low to high



MH / MG SERIES	Stirring rate	Stirring capacity
MG600H	300~1500 rpm	100~2000 ml x 6



MFD SERIES	Stirring rate
MFD800 (115V)	50~1600 rpm
MFD810 (220V)	50~1600 rpm



MFH SERIES	Stirring rate	Temp. control range (hot plate)
MFH800 (115V)	50~1600 rpm	RT +25°C to 310°C (set in 1°C increments)
MFH810 (220V)	50~1600 rpm	RT +25°C to 310°C (set in 1°C increments)

VENTED BALANCE ENCLOSURES



VBE SERIES	Features	Internal work surface
VBE204/214	* Includes top mounted HEPA / blower filtration and face velocity alarm * Constructed with optically clear 3/8" jeweled acrylic plastic and phenolic base	23.5" wide x 21" deep 597mm x 533mm
VBE306/316		35.5" wide x 21" deep 901mm x 533mm
VBE408/418		47.5" wide x 21" deep 1206mm x 533mm
VBE600/610		59.5" wide x 21" deep 1511mm x 533mm

WATER PURIFICATION SYSTEMS

Auto Still: The Distilled Water Model



WG SERIES	Purified water/Quality	Delivery Rate	Tank capacity
WG205	Deionized water: Type 1	~1.0 L/min	20L
	Distilled water: Type 2	~1.5 L/min	



WG SERIES	Purified water/Quality	Delivery Rate	Tank capacity
WG253	Deionized water: Type 1	~1.0 L/min	30L
WG1013	Distilled water: Type 2	~2.5 L/min	100L

Pure Line: The Economical Deionized Model



WE SERIES	Purified water / Quality	Delivery Rate
WE200	Deionized water: Type 1	0.5~1.0 L/min

WATER PURIFICATION SYSTEMS

Auto Pure: The Flagship Deionized Model



WA 400/200 SERIES	Purified Water/Water Quality	Delivery Rate
	Deionized water: Type 1	4.0 L/min



WH SERIES	Purified Water/Water Quality	Delivery Rate
	Deionized water: Type 2 & 3	1.9 L/min or 4.7 L/min depending on model



WA 300 SERIES	Purified water / Water quality	Delivery Rate
	Deionized water: Type 1	2.5 L/min

Available in benchtop or remote dispense configuration



WC SERIES	Purified water / Water quality	Delivery Rate
	Deionized water: Type 1	2.5 L/min

Designed with ultraviolet oxidation lamp
Available in benchtop or remote dispense configuration



WB SERIES	Purified water / Water quality	Delivery Rate
	Deionized water: Type 1	2.0 L/min

Designed with ultrafiltration module
Available in benchtop or remote dispense configuration



WG SERIES	Purified water / Water quality	Delivery Rate
	Deionized water: Type 1	2.0 L/min

Designed with ultraviolet oxidation lamp and ultrafiltration module
Available in benchtop or remote dispense configuration